

DOLCECLIMA® S1 14 HP UL






DOLCECLIMA® S1 14 HP UL Code 01911



FEATURES

Cooling capacity: 14.000 BTU/hr
EER: 2,9
Practical wheels
Practical side handles
Refrigerant gas: R410A
Touch LCD display

FUNCTIONS


-  **Fan mode**
Adjustable 3 fan speed. Fan only mode can also be used.
-  **Dehumidification mode**
-  **Auto mode**
Automatic operation which regulates cooling in relation to the ambient temperature to optimize energy consumption.
-  **Sleep mode**
Gradually increases the temperature set and ensures reduced noise for greater wellbeing at night.
-  **Turbo mode**
Maximum fan speed.
Extra cool.

Application area:
up to 500 sq. ft.



TOUCH DISPLAY

the most advanced technology for optimized cooling performances.



MOTORIZED FLAP

For customised management of the air flow.



ITALIAN DESIGN

first time in the USA



REMOTE CONTROL



HEAT PUMP

traditional heating can be replaced or made more powerful (the condensate drain is necessary in heat pump mode).

PRELIMINARY TECHNICAL DATA

			DOLCECLIMA S1 14 HP UL
	Product code		01911
	Barcode		8021183019117
	Power supply	V-Ph-Hz	115V,1Ph,60Hz
Cooling	Capacity	Btu/hr	14000
	Input	W	1415
	Current	A	12,3
	EER	W/W	2.9
		Btu/W.h	
Heating	Capacity	Btu/h	11000
	Input	W	1170
	Current	A	10.2
	COP	W/W	2.76
Cooling (DOE)	SACC	Btu/h	9000
	Input	W	1300
	Current	A	11.3
	Standby power_DOE	W	1.45
	Off-cycle_DOE:	W	82
	Moisture Removal (35/28.3)	L/h	2.68
	Starting current	A	54
	Indoor side air flow (Hi/Mi/Lo)	m³/h	520/480/443
		CFM	306/283/261
	Indoor side noise level(Hi/Mi/Lo)	dB(A)	56/54/52
	Refrigerant type / quantity	/ oz	R410A / 19,78
	Plug type		LCDI(5-15P)
	Power cord type	AWG	14x3
	Power cord length	mm	1900
	Power cord length	ft	6,2
	Control type		Remote Control
Operation temp (room temp.)	°C	17-35/5-30	
	°F	41-86	
Application area Cooling Standard)	m²	19-27	
Application area Cooling Standard)	sq.ft	205-291	
recommended room size	sq.ft	500	
Dimension (W*D*H)	mm	490x425x765	
	in	19.3/16.7/30.1	
Packing (W*D*H)	mm	535x487x890	
	in	21.1/19.2/35	
Net/Gross weight	Kg	35.0/39.9	
	lb	77.2/88.0	
Loading quantity 20' /40' /40'HQ	Pieces	96/192/288	